

**CLAYTON FIRE COMPANY NO.1 INCORPORATED  
STANDARD OPERATING GUIDLINE # II-2**

Date of Effect: March 1, 1991	To be reviewed: January, 2020
To: All Members	Revised: January 1, 2019
Ordered By: Alexander C Carrow, Fire Chief	
Subject: <b>AUTOMOBILE AND LIGHT DUTY VEHICLE FIRES</b>	

This guideline shall take effect immediately and shall remain in effect until superseded.

**Purpose:** To establish procedures for maximizing firefighter safety when dealing with automobile or other light duty vehicles when involved in fire.

**I. POSITIONING OF APPARATUS**

Apparatus arriving at the scene shall be positioned at a safe distance from the vehicle that is on fire.

**II. APPROACH**

Firefighters approaching the vehicle shall stay clear of any unsafe areas. They will also wear Full PPE & SCBA.

**III. SAFETY**

If there is any type of fire showing, a minimum of one (1), 13/4 line will be pulled. Under no condition should the fuel filler cap be removed. This may permit heated gasoline vapors to escape thus increasing the danger to personnel. Firefighters shall anticipate:

1. Extra fuel tanks
2. Exploding fuel tanks
3. LPG or CNG fuel cylinders
4. Airborne bumpers
5. Exploding driveshafts
6. Exploding tires
7. Exploding batteries
8. Hazardous contents
9. Occupants still in vehicle

**IV. SECURE VEHICLE**

If vehicles tires are still intact use wheel chocks from fire apparatus to limit any movement while completing overhaul.